

Declaration of Performance Nr. 1de 3560v1			
1	Unique identification code of the product type	U brick category I, 240 x115 x 71 mm	
2	Type-, batch- or serial number or any other element allowing identification of the construction product as required purs. to 11 (4)	Article no. 3560 NF	
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	for use in protected or unprotected masonry walls, columns and partitions	
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)	DEPPE Backstein-Keramik GmbH, Neuenhauser Str. 82, D-49843 Uelsen	
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2)	Not applicable	
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	2+	
7	The notified testing laboratory CPD 0854 ( Cert Baustoffe GmbH, 23966 Wismar) performed the initial testing, the determination of the product-type on the basis of type testing (based on sample-tests carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product and issued test report no.2510 - CPR - 323.		
8	Not applicable		
9	<b>Declared performance</b>		
	<b>Main features</b>		<b>Declared performance</b>
	dimensions [mm]	length/width/height	<b>240*115*71</b>
	dimensional tolerances	mean	Tm (+5/-10   +/- 5   +/- 2 mm)
		range	Rm (10   6   3 mm)
	shape and formation		<b>Shape b) i.a.w. 5.3.2</b>
	compressive strength [N/mm <sup>2</sup> ]	category	<b>Category I</b>
		mean	<b>≥ 32</b>
		direction of load	perpendicular to horizontal joint
	moisture movement		<b>NPD</b>
	bond strength		<b>NPD</b>
	active soluble salts content		<b>S2</b>
	reaction to fire		<b>A1</b>
	water absorption (mass %)		<b>6</b>
	water vapour permeability		<b>5/10</b>
	gross dry density	mean	<b>1754</b>
			thermal conductivity
	durability against freeze/thaw: freeze/thaw resistance		<b>F2</b>
	dangerous substances		<b>i.a.w. ZA.3</b>
			<b>Harmonised technical specification</b>
			<b>DIN EN 771-1</b>
			<b>DIN EN 998-2</b>
			<b>DIN EN 771-1</b>
			<b>DIN EN 771-1</b>
			<b>DIN EN 1745</b>
			<b>DIN EN 771-1</b>

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Dr. Dirk Deppe, Uelsen, 09.06.2017