

<b>Declaration of Performance Nr. 1de 7544v1</b>			
1	Unique identification code of the product type	U brick category I, 240 x115 x 71 mm	
2	Type-, batch- or serial number or any other element allowing identification of the construction product as required purs. to 11 (4)	Article no. 7544 NF	
3	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	for use in protected or unprotected masonry walls, columns and partitions	
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)	DEPPE Backstein-Keramik GmbH, Neuenhauser Str. 82, D-49843 Uelsen	
5	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2)	Not applicable	
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	2+	
7	The notified testing laboratory CPD 0854 ( Cert Baustoffe GmbH, 23966 Wismar) performed the initial testing, the determination of the product-type on the basis of type testing (based on sample-tests carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product and issued test report no.2510 - CPR - 323.		
8	Not applicable		
9	<b>Declared performance</b>		
	<b>Main features</b>	<b>Declared performance</b>	<b>Harmonised technical specification</b>
	dimensions [mm]	length/width/height <b>240*115*71</b>	<b>DIN EN 771-1</b>
	dimensional tolerances	mean Tm (+5/-10   +/- 5   +/- 2 mm)	
		range Rm (10   6   3 mm)	
	shape and formation	<b>Shape b) i.a.w. 5.3.2</b>	
	compressive strength [N/mm <sup>2</sup> ]	category <b>Category I</b>	
		mean >=19	
		direction of load perpendicular to horizontal joint	
	moisture movement	<b>NPD</b>	
	bond strength	<b>NPD</b>	<b>DIN EN 998-2</b>
	active soluble salts content	<b>S2</b>	<b>DIN EN 771-1</b>
	reaction to fire	<b>A1</b>	
	water absorption (mass %)	<b>6</b>	<b>DIN EN 771-1</b>
	water vapour permeability	<b>5/10</b>	<b>DIN EN 1745</b>
	gross dry density	mean <b>1705</b>	<b>DIN EN 771-1</b>
		thermal conductivity <b>NPD</b>	
	durability against freeze/thaw: freeze/thaw resistance	<b>F2</b>	
	dangerous substances	<b>i.a.w. ZA.3</b>	

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Dr. Dirk Deppe, Uelsen, 09.06.2017